

IDRAIR/10 19N

Per mandata di aria calda dal compressore alle cisterne per il trasporto anche di prodotti alimentari pulverulenti. Coefficiente di sicurezza 1:10.

Mandrel built delivery hose designed for conveying hot air from compressors to tank trucks used for bulk food. Safety factor 1:10.



Caratteristiche tecniche

Sottostrato	Liscio in gomma bianca resistente al calore e rispondente agli standard F.D.A. e alle direttive BGA / BGVV cat. 3.
Rinforzi	Inserzioni di fibre in poliestere
Copertura	In gomma nera resistente all'abrasione, al calore, agli agenti atmosferici ed all'ozono. Superficie liscia ad impressione tela.
Temperatura	-40 °C +120 °C
Marcatura	 THOR - HOT AIR +120°C (in lettere rosse)

Technical Characteristics

Tube	White smooth, heat resistant rubber. Complying with FDA standards and with BGA/BgVV recommendations cat 3.
Reinforcement	High tensile textile plies
Cover	Black, smooth rubber, resistant to abrasion, weather, heat and abrasion. Fabric impression.
Temperature	-40 °C +120 °C
Marking	 THOR - HOT AIR +120°C (in red letters)

Misure / Sizes

Diametro interno Inner Diameter	Diametro esterno Outside Diameter	Pressione di esercizio Working Pressure	Pressione di scoppio Nominal Burst Pressure	Peso teorico Weight
mm	mm	bar	bar	Kg/m
51	67	3	43	1,85
60	76	3	37	2,10
64	80	3	35	2,22